


Dichtungsscheiben

passend zu Kabelverschraubungen Syntec®



Material: Perbunan
Einsatztemperatur: -20°C / +100°C

Sealing washer

suitable for cable glands Syntec®

Material: Perbunan
Temperature range: -20°C / +100°C



zu Anschlussgewinde metrisch

suitable for metric entry thread

Art.-Nr.	G	ØD1 mm	ØD2 mm	M mm
1012.45.16	M12	20	12	1.6
1017.45.16	M16	23	16	1.8
1020.45.16	M20	29	20	1.8
1025.45.16	M25	37	25	1.8
1032.45.16	M32	44	32	2.2
1040.45.16	M40	52	40	2.2
1050.45.16	M50	64	50	2.7
1063.45.16	M63	68	63	3.2

zu Anschlussgewinde Pg

suitable for entry thread Pg

Art.-Nr.	G	ØD1 mm	ØD2 mm	M mm
1007.45.16	Pg 7	16.0	11.5	2.0
1009.45.16	Pg 9	19.0	14.0	2.0
1011.45.16	Pg 11	22.5	18.5	2.0
1013.45.16	Pg 13	25.0	19.0	2.0
1016.45.16	Pg 16	27.0	21.0	2.0
1021.45.16	Pg 21	34.0	27.0	2.5
1029.45.16	Pg 29	43.0	35.0	2.5
1036.45.16	Pg 36	54.0	45.0	2.5

Blindscheiben passend zu Progress®
Kabelverschraubungen

Blind discs suitable for Progress®
cable glands

Material: Polyamid
Einsatztemperatur: -20°C / +100°C
Einsatzbereich: Staubverschluss zu
Kabelverschraubungen

Material: Polyamide
Temperature range: -20°C / +100°C
Application: Dust stopper for cabl



Blindscheibe als Staubschutz

Blind disc for dust protection

Art.-Nr.	G	Ø mm	M mm
1012.00.19	M10 / M12 / Pg 7	10.5	0.3
1017.00.19	M16 / Pg 9	13.5	0.3
1011.00.19	Pg 11	16.5	0.3
1020.00.19	M20 / Pg 13 / Pg 16	20.5	0.3
1025.00.19	M25 / Pg 21	26.5	0.3
1029.00.19	Pg 29	35.0	0.3
1032.00.19	M32	30.0	0.3
1036.00.19	Pg 36	45.0	0.3
1040.00.19	M40	38.0	0.3
1050.00.19	M50 / Pg 42	52.0	0.3
1063.00.19	M63 / Pg 48	57.0	0.3