


## O-Ring passend zu Progress Metall-Kabelverschraubung

## O-ring suitable for metal cable gland Progress

Material: NBR  
Einsatztemperatur: -40°C / +100°C

Material: NBR  
Temperature range: -40°C / +100°C



zu Anschlussgewinde metrisch oder Pg

suitable for entry thread metric or Pg



Art.-Nr.	G	ID mm	D mm	
1005.00.08	M 6	5.0	1.0	1
1006.00.08	M 8	6.0	1.5	1
1006.06.08	M10	8.1	1.6	1
1007.00.08	M12/Pg7	10.0	1.5	1
1000.09.00.08	M16/Pg 9	13.1	1.6	1
2111.00.08	M20	17.0	2.0	1
1013.00.22.08	M25	22.0	2.0	1
1021.00.30.08	M32	30.0	2.0	1
1000.40.00.08	M40	36.0	2.0	1
1000.50.00.08	M50	46.0	2.0	1
1000.63.00.08	M63	60.0	2.0	1
1000.75.00.08	M75	72.0	2.0	1
1011.00.08	Pg 11	15.0	2.0	1
1016.00.08	Pg 16	19.0	2.0	1
1016.00.25.08	Pg 21	25.0	2.0	1
1029.00.08	Pg 29	33.0	2.2	1
1036.00.08	Pg 36	42.5	2.6	1
1000.42.00.08	Pg 42	48.0	3.0	1
1000.48.00.08	Pg 48	55.0	2.0	1

## O-Ring passend zu Progress Metall-Kabelverschraubung

## O-ring suitable for metal cable gland Progress

Material: FPM  
Einsatztemperatur: -25°C / +200°C

Material: FPM  
Temperature range: -25°C / +200°C



zu Anschlussgewinde metrisch oder Pg

suitable for entry thread metric or Pg

Art.-Nr.	G	ID mm	D mm	
1105.98.08	M 6	5.0	1.0	1
1106.98.08	M 8	6.0	1.8	1
1106.06.98.08	M10	8.1	1.6	1
1107.98.08	M12/Pg7	10.0	1.5	1
1100.09.98.08	M16/Pg9	13.1	1.6	1
2111.98.08	M20	17.0	2.0	1
1113.98.22.08	M25	22.0	2.0	1
1121.98.30.08	M32	30.0	2.0	1
1100.40.98.08	M40	37.8	2.6	1
1100.50.98.08	M50	46.0	2.0	1
1100.63.98.08	M63	60.0	2.0	1
1100.75.98.08	M75	72.0	2.0	1
1111.98.08	Pg 11	15.0	2.0	1
1116.98.08	Pg 16	18.0	2.0	1
1116.98.25.08	Pg 21	25.0	2.0	1
1129.98.08	Pg 29	33.0	1.8	1
1136.98.08	Pg 36	42.5	2.6	1
1100.42.98.08	Pg 42	48.0	3.0	1
1100.48.98.08	Pg 48	55.0	2.0	1