


# Kabelverschraubungen Progress® EMV Messing mit Kontakthülse

## Cable glands Progress® EMC nickel-plated brass with contact sleeve

### Kurzes Anschlussgewinde metrisch | Short entry thread metric



Material: Messing vernickelt  
 Kontakthülse: Messing vernickelt  
 Dichtung: TPE  
 O-Ring : NBR  
 Zugentlastung: Nach EN 50262 Ausführung A  
 Einsatztemperatur: -40°C / +100°C  
 Schutzart: IP 68 (bis 10 bar)  
 Schutzart Zusatz: IP 69K  
 Eigenschaften: Sehr guter Schirmkontakt über die Kontakthülse bei in der Kabelverschraubung endendem Schirmgeflecht

Material: Nickel-plated brass  
 Contact sleeve: Nickel-plated brass  
 Seal: TPE  
 O-ring : NBR  
 Strain relief: According to EN 50262 version A  
 Temperature range: -40°C / +100°C  
 Protection class: IP 68 (up to 10 bar)  
 Protection type addition: IP 69K  
 Properties: Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland





### Progress MS EMV



Einteiliger Dichteinsatz  
 nicht durchgehend isolierend

One-piece sealing insert  
 not overall length insulated

G	>Ø< min mm	>Ø< max mm	 mm	H mm	L mm	i info	Art.-Nr.   Art. no.	
M8x1.25	2.5	3.5	11	15	5	1	1080.08.035	50
M8x1.25	3.0	4.0	11	15	5	1	1080.08.040	50
M10x1.5	3.0	4.0	13	16	5	1	1080.10.040	50
M10x1.5	4.0	6.0	13	16	5	1	1080.10.060	50
M12x1.5	4.5	6.0	15	20	5	-	1080.12.060	50
M12x1.5	6.0	7.5	15	20	5	-	1080.12.075	50
M16x1.5	6.0	8.0	18	23	5	-	1080.17.080	50
M16x1.5	8.0	10.0	18	25	5	-	1080.17.100	50
M20x1.5	8.0	11.0	24	25	6	-	1080.20.110	50
M20x1.5	11.0	14.0	24	27	6	-	1080.20.140	50
M25x1.5	13.0	16.0	30	30	7	-	1080.25.160	25
M25x1.5	16.0	19.0	30	33	7	-	1080.25.190	25
M32x1.5	18.0	21.0	36	32	8	-	1080.32.210	25
M32x1.5	21.0	25.0	36	32	8	-	1080.32.250	25
M40x1.5	24.0	28.5	46	34	8	-	1080.40.285	10
M40x1.5	28.5	32.0	46	34	8	-	1080.40.320	10
M50x1.5	33.0	37.0	55	36	9	-	1080.50.370	10
M50x1.5	37.0	41.0	55	36	9	-	1080.50.410	10
M63x1.5	40.0	46.0	70	39	10	-	1080.63.460	5
M63x1.5	46.0	50.0	70	39	10	-	1080.63.500	5
M75x1.5	50.0	56.0	80	40	11	-	1080.75.560	1
M80x2.0	56.0	65.0	95	45	18	-	1080.80.650	1
M85x2.0	63.0	70.0	95	45	18	-	1080.85.700	1
M95x2.0	68.0	75.0	110	52	20	-	1080.95.750	1

1 = Metrisches Regelgewinde

1 = Metric coarse-pitch thread